SocketModem® HSDPA

Embedded Wireless Modem




Universal Socket Benefits

- Interchangeable communications devices
- Quick-to-market
- Global approvals
- Easy migration to future networks

The SocketModem® HSDPA wireless modem is a complete, ready-to-integrate communications device that offers standards-based tri-band UMTS/HSDPA performance. This quick-to-market communications device allows developers to add wireless communication to products with a minimum of development time and expense. The SocketModem HSDPA wireless modem is based on industry-standard open interfaces and utilizes Multi-Tech's universal socket design.

Features

- Tri-band UMTS/HSDPA 3.6
- Quad-band GSM/GPRS/EDGE
- Supports Short Message Service such as text and PDU mode, point-to-point (MT/MO) and cell broadcast
- GSM circuit-switched data up to 9600 bps and UMTS circuitswitched data up to 64K bps
- MMCX antenna connector and SIM socket
- USB 2.0 full speed interface or standard serial interface
- Serial interface supports DTE speeds to 921.6K bps*
- FCC, PTCRB and R&TTE certified
- AT command compatible
- Universal socket connectivity
- Two-year warranty
- * Effective throughput is 700 750K bps.







Highlights

Applications. With download packet data speeds over 1M bps, the SocketModem HSDPA wireless modem will support highly data-intensive applications such as remote video surveillance and other multimedia applications where you are sending digital images, web pages and photographs.


Integration Reduces Space, Power and Cost. The SocketModem HSDPA wireless modem integrates the controller, RF transceiver, and antenna interface in one communications device. This integration requires low power, low real estate and provides an overall reduction in costs.

Reduces Development Time. The SocketModem HSDPA wireless modem enhances your product while you focus on developing its core features. It actually provides faster timeto-market because it relieves the burden and expense of obtaining PTCRB and RF approvals.

SocketModem HSDPA Pin-Out. The SocketModem

HSDPA wireless modem interfaces easily with existing products through a standard serial

communication channel or USB interface. The serial DTE channel is capable of transfer speeds to 920K bps and can be interfaced directly to a UART or microcontroller. The complete on-board RF transceiver interfaces with an antenna for direct connection to wireless SMS, circuitswitched dial-up, or packet data networks.



Universal Socket Connectivity. Multi-Tech's universal socket is a flexible, comm-port architecture that provides cellular, Ethernet, PSTN or Wi-Fi network access with interchangeable communications devices. This means you can utilize one system design and populate it with your connectivity device of choice accommodating multiple connectivity requirements. In addition, you are assured a seamless migration to future technologies.

Ordering Information

ProductDescriptionRegionMTSMC-HTri-band HSDPA Serial ModemGlobalMTSMC-H-UTri-band HSDPA USB ModemGlobal

Made in Mounds View, MN, U.S.A.

Features and specifications are subject to change without notice.

Trademarks / Registered Trademarks: SocketModem, Multi-Tech, and the Multi-Tech logo: Multi-Tech Systems, Inc. / All other products and technologies are the trademarks or registered trademarks of their respective holders.

Developer's Kit. The Developer's Kit allows you to plug in the communications device and use it for testing, programming and evaluation. The kit includes one development board with RS-232 DB-25 connector, USB connector, universal power supply, antenna, RS-232 and USB cables.

Specifications

General Features

Tri-band UMTS/HSDPA (WCDMA/FDD), 850/1900/2100 MHz, UMTS/HSDPA 3GPP release 5

HSDPA: 3.6M bps max. download, 384K bps max. upload UMTS: 384K max. download, 384K bps max. upload Quad-band GSM/GPRS/EDGE, 850/900/1800/1900 MHz

Packet Data Features

HSDPA: UE CAT [1-6], 11, 12 supported, Compressed mode according to 3GPP TS25.212

EDGE: Class 10, Modulation & coding schemes MCS 1-9, Mobile station Class B

GPRS: Class 10, full PBCCH support, coding schemes CS 1-4, Mobile station Class B

Circuit Switched Data Features

GSM: Asynchronous, non-transparent up to 9600 bps (V.110)

UMTS: Asynchronous, non-transparent up to 64K bps (V.120)

SMS Features

Text & PDU, Point-to-Point (MO and MT), cell broadcast

Connectors

Antenna: MMCX

SIM: Standard 3V SIM receptacle

USB Interface

USB 2.0 full speed

CDC ACM compliant

NDIS driver available (XP and Vista)

Power Requirements

5VDC; 930mA maximum (HSDPA mode) See developers guide for additional requirements

Physical Description

3.1" L x 1.4" W x 0.5" H; 1 oz. (7.8 cm x 3.5 cm x 1.2 cm; 28 g)

Operating Environment

N------1 0--------- 200 t- - - F00

Normal Operation: -30° to +50° C

Certifications

CE Mark, R&TTE

EMC: FCC Part 22, 24, EN 301 489-1, EN 301 489-7, RSS

132, 133

Safety: UL 60950-1, EN 60950-1, AS/NZS 60950:2000

Network: PTCRB

World Headquarters Tel: (763) 785-3500 (800) 328-9717

(800) 328-9717 www.multitech.com **EMEA Headquarters**

Multi-Tech Systems (EMEA) United Kingdom

Tel: +(44) 118-959 7774

Multi-Tech Systems (EMEA) France

Tel: +(33) 1 49 19 22 06

